

RS148 Data Center Server Cabinet



Features

- All doors open 180°
- No internal airflow recirculation
- Locking, removable side panels

Specifications

Unit Server Cabinet includes

- Locking cabinet door with 4 point latch system for added security
- Pairs of split, locking, and removable side panels. Split panels are more versatile for removing
- Pairs of 19in EIA-310-D complaint square hole punched rails (adjustable in 1" increments) with rack unit markings
- Removable top panels for additional cable entry
- Adjustable leveling feet
- Recessed casters allows for clearance through a standard height doorway
- Casters can be removed

PDU & Cable Management Bars

- Compatible with tool-less button style PDUs
- Adjustable cable management bars
- Lances for making cabling easier

Dimensions

- Rack Units: 42U or 48U
- Depth: 42" or 48"
- Width: 24"

Weight Capacity

- Static Load: 3,000 lbs
- Floor mounting bracket or casters and levelers.

Vertical Mounting Post

- 3/8" square hole
- RU Markings
- Mounting depth adjustable 24" - 30" in 1" increments
- Mounting depth preset to 29"

Frame

- Cold rolled steel, 13 Ga
- Matte black, powder coat, medium texture

Doors

- Doors Pivot 180°
- Full doors (front and rear)
- Tool-less install and reversible
- Latch: 1/4 turn swing handles, front and rear
- Lock: Single key code, multiple key, master
- Locking mechanism: Single door is 4 point hook

Top & Bottom Panels

- Solid, round holes, and rectangular openings
- Grommets and hole caps available
- Optional KoldLok air seals

RackSolutions.com

Toll Free: 1-888-903-7225 | Email: info@racksolutions.com