DC Rack Model 151SW



Features

- Constructed in 16-gauge steel
- Meets PCI DSS (Payment Card Industry Data Security Standard) compliance requirements
- Inside rear of cabinet includes two (2) tool-less PDU cable tray for cable management and industry standard vertical PDU installation.
- Locking, removing, reversable, front and rear doors, cabinet doors feature a minimum 65% airflow perforation pattern that meets or exceeds equipment manufacturer requirements.
- Top panel is easily removable for cable installation. The generous cable access panels makes it easy to install top panel without affecting installed cabling.
- Locking, removable side panels
- •Built in joining kit speeds up baying of multiple cabinets within a row

Specifications

1 (1) Unit Server Cabinet includes:

- (1) locking front cabinet door with curved surface for added stability
- (2) pairs of split, locking, and removable side panels. Split panels are more versatile for removing.
- (2) pairs of 19in EIA-310-D complaint square hole punched rails with rack unit markings. Rails easily in depth in 1/4" increments
- (2) tool-less PDU cable tray
- (6) hinged plastic cable grommets on top panel
- (2) removable top panels for additional cable entry
- (4) adjustable leveling feet
- (4) recessed casters allows for clearance through a standard height doorway. Casters can be removed.

Tested to 3,000 lbs (1,360 kg) of equipment load RoHS Compliant

Available U	Size
151SW-4560	24U, 600 width, 1070 depth
151SW-4561	32U, 600 width, 1070 depth
151SW-4562	37U, 600 width, 1070 depth
151SW-4563	42U, 600 width, 1070 depth
151SW-4565	42U, 600 width, 1200 depth
151SW-4566	48U, 600 width, 1200 depth
151SW-4567	48U, 800 width, 1200 depth
151SW-4569	42U, 800 width, 1200 depth
151SW-4571	32U, 600 width, 1070 depth without lock



www.RackSolutions.co.uk

Toll Free: +44 (0) 1925-454093 | Fax: +44 (0) 1925-454093 | Email: ukinfo@racksolutions.com