

	1UKIT-109-31	2UKIT-109-31	3UKIT-109-31
Front View	<p>19.00 [482.6] 17.40 [442.0] Maximum Equipment Width 16.37 [415.8] Minimum Equipment Width 1U (1.74) [44.2] 0.046 [11.7] Material Thickness 1.13 [28.7]</p>	<p>19.00 [482.6] 17.40 [442.0] Maximum Equipment Width 16.38 [416.1] Minimum Equipment Width 2U (3.48) [88.4] 0.046 [11.7] Material Thickness 1.38 [35.2]</p>	<p>19.00 [482.6] 17.40 [442.0] Maximum Equipment Width 16.75 [425.5] Minimum Equipment Width 3U (5.23) [132.8] 0.056 [14.2] Material Thickness 1.44 [36.7]</p>
Rail Interior View	<p>31.00 [787.4]</p>	<p>31.00 [787.4]</p>	<p>31.00 [787.4]</p>
Rail Exterior View	<p>11.00 [279.4] Minimum Mounting Depth 38.14 [968.8] Maximum Mounting Depth <math>\phi 1.00</math> [25.4]</p>	<p>11.00 [279.4] Minimum Mounting Depth 38.14 [968.8] Maximum Mounting Depth <math>\phi 2.00</math> [50.8]</p>	<p>11.00 [279.4] Minimum Mounting Depth 38.14 [968.8] Maximum Mounting Depth <math>\phi 2.00</math> [50.8]</p>
4 Post Mount Overview			

**Note: Cable Bar cannot be used on Racks less than 31" deep**

ALL DIMENSIONS ARE IN INCHES.  
DIMENSIONS IN SQUARE BRACKETS ARE IN  
[MILLIMETERS] AND FOR REFERENCE ONLY.  
PROPRIETARY AND CONFIDENTIAL